Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claims 1 - 18 (cancelled)

Claim 19 (currently amended): A method of treating and reactivating a sorbent for use in capturing carbon dioxide in a fuel combustion process, wherein the combustion process is performed in a fluidized bed and generates carbon dioxide, and the sorbent comprises a calcinable alkaline earth metal, the method comprising

- (a) calcining the sorbent to form an alkaline earth metal oxide; and thereafter
- (b) introducing the alkaline earth metal oxide into a carbonator at a temperature of at least 600°C, and subjecting the alkaline earth metal oxide to carbon dioxide of a concentration of at least 85% to produce a carbonate of the alkaline earth metal;
 - (c) transferring the alkaline earth metal carbonate into the fluidized bed;
- (d) calcining the alkaline earth metal carbonate to regenerate the alkaline earth metal oxide and carbon dioxide;
 - (e) selectively removing the carbon dioxide produced in step (d); and
- (f) returning the alkaline earth metal oxide product of step (d) to the carbonator to capture carbon dioxide generated in the fuel combustion process; and thereafter
- (g) repeating steps (c) to (f) and selectively repeating step (b) between steps (f) and (c).

Claim 20 (previously presented): The method as defined in claim 1, wherein the carbon dioxide produced in step (d) is pure carbon dioxide.

Claim 21 (previously presented): The method as defined in claim 19, wherein step (b) further produces a residue comprising at least one of spent sorbent material and surplus carbon dioxide, and step (b) further comprises recovering the residue.

Claim 22 (previously presented): The method as defined in claim 19, wherein the alkaline earth metal carbonate is limestone.

Claim 23 (previously presented): The method as defined in claim 19, wherein the alkaline earth metal oxide is lime

Claim 24 (previously presented): The method as defined in claim 19, wherein the fluidized bed comprises a pressurized fluidized bed combustor (PFBC/C).

Claim 25 (previously presented): The method as defined in claim 19, wherein the fluidized bed comprises a circulating fluidized bed combustor (CFBC/C).

Claim 26 (currently amended): A method of treating and reactivating a sorbent for use in capturing carbon dioxide in a fuel combustion process, wherein the combustion process is performed in a fluidized bed and generates carbon dioxide, and the sorbent comprises a calcinable alkaline earth metal, the method comprising

- (a) calcining the sorbent in a first calciner to form an alkaline earth metal oxide;
- (b) treating the alkaline earth metal oxide in a hydration reactor to form an alkaline earth metal hydroxide:
- (c) carbonating the alkaline earth metal hydroxide at a temperature of at least 600°C 700°C and subjecting the alkaline earth metal hydroxide to carbon dioxide of a concentration of at least 85% to produce a carbonate of the alkaline earth metal and water;
- (d) transferring the alkaline earth metal carbonate into a second calciner and calcining the alkaline earth metal carbonate to regenerate the alkaline earth metal oxide and produce carbon dioxide:
- (e) introducing the alkaline earth metal oxide into a carbonator at a temperature of at least 600°C and subjecting the alkaline earth metal oxide to carbon dioxide of a concentration of at least 85% to produce a carbonate of the alkaline earth metal;
 - (f) selectively removing the carbon dioxide produced in step (d);

Appl. No. 10/577,542 Amdt, Dated Aug. 12, 2009

Reply to Final Office Action of Jul. 28, 2009

(g) returning the alkaline earth metal oxide product of step (d) to the carbonator to capture carbon dioxide generated in the fuel combustion process; and thereafter

(h) repeating steps (b), (c), (d), (f) and (g), and selectively repeating step (e) between steps (f) and (g).

Claim 27 (previously presented): The method as defined in claim 26, wherein step (e) further produces a residue comprising at least one of spent sorbent material and surplus carbon dioxide, and step (e) further comprises recovering the residue.

Claim 28 (previously presented): The method as defined in claim 26, wherein the carbon dioxide produced in step (d) is pure carbon dioxide.

Claim 29 (previously presented): The method as defined in claim 26, wherein step (b) is performed using liquid water or steam at a temperature greater than 50°C.

Claim 30 (previously presented): The method as defined in claim 26, wherein step (c) and step (e) are each performed at a temperature in the range of 700°C to 1200°C.

Claim 31 (previously presented): The method as defined in claim 29, wherein step (b) is performed at atmospheric pressure.

Claim 32 (previously presented): The method as defined in claim 29, wherein step (b) is performed at a pressure greater than atmospheric pressure.

Claim 33 (previously presented): The method as defined in claim 26 wherein the alkaline earth metal carbonate is limestone.

Claim 34 (previously presented): The method as defined in claim 26, wherein the alkaline earth metal oxide is lime.

Claim 35 (previously presented): The method as defined in claim 26, wherein the fluidized bed

Appl. No. 10/577,542 Amdt. Dated Aug. 12, 2009

Reply to Final Office Action of Jul. 28, 2009

comprises a pressurized fluidized bed combustor (PFBC/C).

Claim 36 (previously presented): The method as defined in claim 26, wherein the fluidized bed comprises a circulating fluidized bed combustor (CFBC/C).